



SPECIFICATION

Current Rating: 1.0Amp
Insulation Resistance: 1000MΩ min
Contact Resistance: 20MΩ max
Withstand Voltage: 500V AC/DC
Operating Temperature: -40°C to +105°C
Contact Material: Brass
Contact Plating: Au or Sn Over Ni
Insulator Material: PA6T+30%GF UL 94V-0

Ordering Code:

LHBS02 - X - X - X - X - X - X - X
① ② ③ ④ ⑤ ⑥ ⑦ ⑧

① Series No:

② No. of Contacts

10 12 14
16 20 24
26 30 32
34 40 44
50 60 64
80 100

③ Contact Plating:

G0:Gold flash S0:Selective
G1:3U" Gold S1:Selective 3u"
G2:5u" Gold S2:Selective 5u"
G3:10u" Gold S3:Selective 10u"
G4:15u" Gold S4:Selective 15u"
G5:30u" Gold S5:Selective 30u"
SN:Tin

④ Color Insulator

B:Black
U:Blue
W:White

⑤ Insulator Material

B:PA6T
C:LCP
E:PA9T





⑥ Packing

A:Tray
B:Bag
T:Tube
U:Tube+CAP
R:Tape&Reel
W:Tape&Reel+CAP

⑦ A: Type 1

B: Type 2

Recommended P.C.B Layout(Top Side)
(PCB BOARD TOLERANCE±0.05)



SECTION A-A

Unless Otherwise specified tolerance
X. ±0.35 X.XX: ±0.20
X.X: ±0.25 X.XXX: ±0.15

SCALE: As Shown UNIT: mm

DRAW YG ZHONG DATE 01/05/2016

CHECK BobYang DATE 01/05/2016



ANTENK ELECTRONICS CO., LTD
Http://www.antenk.com
E-mail:sales@antenk.com

TITLE:

1.27*2.54mm Ejector Header 180° Four Row Foot

DRAWING NO:

LHBS02-XXXXX

PRODUCT NO:

LHBS02-XXXXX

REV

DESCRIPTION

DATE